



Assembly Instructions

AH-SCL – Starter Coop Large

List of parts in fixings pack

- 10 x 20mm Screws
- 17 x 60mm Screws
- 1 x 1000mm Rope
- 2 x Cabin Hook
- 1 x Cleat



Attach the back panel to one side panel using 2x 60mm screws repeat for the other side

(Screw through the frame of the side panel into the back panel).

Next slot the ply base into position.

Screw the front panel with door, into place using 4x 60mm screws. Then place the roof on.

Assembling the run section. Fix the front panel of run inside one of the side panels, and repeat this for the other side panel. (Take note of photograph regarding the left and right side panels; the small blocks need to face inwards and be positioned in the same way as the photograph).



Fix the top of the run into place using 5x 60mm screws. (2x screws into the framing of each long section and one in the centre of the frame screwing into the front panel of the run).

Place the run against the coop & fix the cabin hooks into place with 8x 20mm screws.

Finally screw the cleat to the front of the roof with 2x 20mm screws.



IMPORTANT CUSTOMER INFORMATION

Pressure preservative treatment is designed to prevent rot and insect attack for up to 15 years and to give softwood timber products an extended and low maintenance service life. The treatment is not intended to perform as a waterproofing agent. The dry, external timbers can have a water ingress protection added with the application of an appropriate and well maintained water repellent coating. This would involve a proprietary water repellent coating product which could be applied to the dry external timbers following the relevant manufacturer's guidelines. Recommended products include Thompson's WaterSeal, Hickson Decor Wax Coat and RESTOL Wood Oil.

To minimise twisting and warping all Hutton garden products should only be used on firm level ground. Softwood is a natural material which can twist and split during periods of wet/dry, hot/cold weather. If cracks do appear it is a natural occurrence and not a fault with the product or material. The best way to treat this is to use a cloth and rub a little PVA wood glue into the crack and once dry sand the area lightly.

Product Care

All Hutton products, where appropriate, come with easy to follow instructions. Please take time to read these carefully before assembling.

Hutton products are built to last with high quality timber to refined designs. Joinery standards are second to none with professional carpenters using pressure treated softwood that offers long-lasting protection against rot, insect and fungal attack.

Although the TANALITH wood preservative used in the pressure-treatment process is of the highest quality, it doesn't protect timber from the effects of weather.

Without additional protection UV rays from the sun will weather timber changing the colour to silvery grey. Moisture will negatively affect the lifespan and performance of a timber product, so it's essential to add a high-quality protective water-repellent coating to your Hutton product.

Here are our tips and advice for getting the best out of your product.

-  Softwood is a natural product that can twist or warp through changes in climatic conditions. To minimise this, Hutton products should always be sited on firm and level ground that is away from areas where water collects.
-  During the pressure-treatment process, some grain may be raised. If desired this can be removed with a little light sanding.
-  Green marking may become visible as salt leaves the timber whilst it dries following pressure treatment. It will fade over time and does not affect the performance of the product. Remove any of this solid salt residue with a wire brush or light sanding prior to painting. A micro-porous (breathable) coating will allow any further moisture to evaporate out through the paint.
-  Changes in the weather may cause fixings to loosen but these can be tightened up as appropriate.
-  Softwood may at times develop cracks in the surface called 'shakes'. These are a natural occurrence and can be prevalent during changes in temperature and humidity as the timber expands and contracts. Please note that this will not affect the performance or durability of your product. If desired, any 'shakes' can be rectified by applying a proprietary wood glue making sure to follow the manufacturer's instructions at all times. Once dry this can be sanded to a smooth finish. Application of a high-quality protective water-repellent coating can reduce cracking by stopping moisture penetrating into the timber, one of the causes of this natural process in timber products.
-  Over time the colour of your Hutton product will gradually weather, first to a honey brown and then to a silver grey. This does not indicate any loss of preservative protection. To keep the original colour of your timber you will need to apply a clear wood paint, oil, or stain, that has UV blockers to stop the greying process.
-  A quality wood paint or oil can be applied to your product to provide protection and colour. Garden designs can benefit from a coloured timber product whether it be a bench, arch, arbour or building, complimenting planting and adding year-round colour. Apply in dry weather and follow the manufacturer's full recommendations.
-  Some staining can occur on paint coatings as tannins and/or sap/resin come out of the new timber. This is a natural process but a stain-blocking primer and/or knotting agent can be applied prior to painting to minimise potential staining.
-  Pressure treated products can be painted with a high-quality wood treatment as long as the moisture content is below 18%. Always check with the manufacturer as some treatments can cause the timber to warp or split if it hasn't fully dried.
-  Sheds are pressure treated but will need additional protection from the weather and in particular, moisture penetration. Apply a high-quality water-repellent paint or oil to help seal the shed, making sure that joints and fixings such as nails and screws, are well covered. A good microporous coating will allow any internal moisture to evaporate out through the external coating.
-  When applying a wood paint, oil, or stain, pay particular attention to horizontal surfaces and areas that can collect water. Coatings will degrade quickest on a horizontal plane with cheaper products wearing faster. Vertical surfaces can last for years before a maintenance coat is required.
-  Maintain your timber product on an annual basis, or sooner if required. Clean paint coatings with soapy water and apply a maintenance coat when required. The better the quality the more years it will be before a maintenance coat is needed. Untreated timber products should be cleaned with soapy water or a wood cleaner.
-  In the unlikely event a product is faulty or damaged upon delivery, any issue must be advised within a reasonable period. The definition of reasonable depends on the product and how obvious the fault is, however, even with more complex items you should work on the basis that this is no more than three to four weeks from receipt. This does not affect your statutory rights.
-  Whilst your delivery driver is present ensure that you check your shipment before signing the delivery receipt, as notifications of damages or shortages should be noted on the signed proof of delivery.
-  To view our tutorial videos on product maintenance, please visit www.svw2000.co.uk/you-tube-videos

Hutton Garden and Landscaping Products

Church Lane, Northwood Green, Westbury-on-Severn, Gloucestershire GL14 1ND www.svw2000.co.uk/hutton

Tel: 01452 762089

Fax: 01452 760993

office@hutton-ltd.co.uk